



GENERAL NOTES

Existing reinforcing bars to be re-used when possible. Where replacement is necessary, lap new bars of the same size 20 diameters over sound existing steel.

Gunite shall be damp cured for at least 5 days after placing or by proper application of an approved sealing compound.

Gunite shall not be applied when the air temperature is below 50 degrees except with the permission of the engineer in charge.

ESTIMATED QUANTITIES

Sidewalk Repair	1100 Sq. ft.
Guniting	420 Sq. ft.
Hot Poured Rubber Type Joint Filler	220 Ln. ft.
Asphalt	as req'd

DESIGNED BY	L.B. Jackson
DRAWN BY	
TRACED BY	
CHECKED BY	J. Covert
APPROVED:	
HIGHWAY & EXPRESSWAY ENGINEER	

CITY OF DETROIT
DEPARTMENT OF PUBLIC WORKS
CITY ENGINEERS OFFICE
BUREAU OF HIGHWAYS AND EXPRESSWAYS

BRIDGE MAINTENANCE
ROUGE PARK
BW270-SPINOZA DRIVE OVER ROUGE RIVER
REPAIR PLAN

SHEET	OF	SHEETS
JOB No.	M-BW270	
DRWG No.	C101	
DATE	JAN. 1958	