



GENERAL NOTES

Existing reinforcing bars to be re-used when possible. Where replacement is necessary, lap new bars of the same size 20 diameters over sound existing steel.

Gunitite shall be damp cured for at least 5 days after placing or by proper application of an approved sealing compound.

Gunitite shall not be applied when the air temperature is below 50 degrees except with the permission of the engineer in charge.

ESTIMATED QUANTITIES

Sidewalk Repair	1100 Sq. ft.
Guniting	420 Sq. ft.
Hot Poured Rubber Type Joint Filler	220 Lb. ft.
Asphalt	as req'd

CITY OF DETROIT DEPARTMENT OF PUBLIC WORKS CITY ENGINEERS OFFICE BUREAU OF HIGHWAYS AND EXPRESSWAYS		BRIDGE MAINTENANCE		SHEET <u>1</u> OF <u>1</u> SHEETS
DESIGNED BY		DRAWN BY <b>L.B. Jackson</b>		JOB No. M-BW270
TRACED BY		CHECKED BY <b>J. Cover</b>		DRWG No. C101
REVISIONS LOCATED BY COORDINATES ON SHEET		HIGHWAY & EXPRESSWAY ENGINEER		DATE JAN. 1958
BW270 - SPINOZA DRIVE OVER ROUGE RIVER REPAIR PLAN				