



PLUMER

DETAIL OF WALLS (A) (C) (E) (G)
Scale 1/2" = 1'-0"

DETAIL OF WALLS (B) (D) (F)
Scale 1/2" = 1'-0"

DETAIL OF STAIRWAY AT HOUSE # 2394

DETAIL OF STAIRWAY AT HOUSE # 2406

DETAIL OF STAIRWAY ON LOT 39

DETAIL OF STAIRWAY ON LOT 41

GENERAL NOTES.

Locate steps opposite walks along sides of houses.

Build cement walks 4 1/2" thick to porch steps and between present sidewalk and steps as noted.

Provide keys, tar-paper and asphaltic fabric in all vertical joints as per special detail.

Backs of all walls to receive two brush coats of asphalt waterproofing.

Provide 1/4" x 3/8" dowels 12% in all joints between footings and walls. Provide keys in all footings.

Chamfer all exposed corners 1".

All cement mix to be 1:2:3.

Railing on top of walls to be provided if desired and necessary. Location to be decided on in field.

Approved: *[Signature]*
City Engineer

CITY OF DETROIT
DEPARTMENT OF PUBLIC WORKS
Office of City Engineer - Division of Grate Separators & Bridges.
LIVERNOIS AVE. - WALLS - EAST SIDE OF STREET - SOUTH OF PLUMER.

Scale: 1/4" = 1'-0" and as noted August 1932.
Revised: 9-28-33.

Made by: *[Signature]*
Checked by: *[Signature]*