



NOTES FOR AREA - A -
 CONC. TO BE POURED IN STRIPS NOT TO EXCEED 12 1/2 FT. IN WIDTH WITH TRANSVERSE CONTRACTION JOINTS AT 20 FT. SPACING. USE THICKENED EDGES OF 6" TO 8" IN 3 FT.
 EXPANSION JOINT (1/4" JOINT FILLER) TO BE USED AT FULL LENGTH OF WALK EDGE.

NOTES FOR AREA - B -
 SHADED AREA TO BE PAVED. (ADJACENT CONC. COMPLETED BY W.P.A. - 1942)
 EXPANSION JOINTS (1/4" JOINT FILLER) TO BE USED WHERE SHOWN ON PLAN BY DOUBLE LINES - THUS -
 MEET EX. CONCRETE, IF NECESSARY - ADJUST ELEVATIONS SHOWN TO PROVIDE PROPER DRAINAGE.

FURTHER INFORMATION WILL BE FURNISHED LATER

| | | | |
|-------------|--------------------|--------------------|----------------------|
| DESIGNED BY | E.E. Stojanovic | APPROVED | J.L. Barton |
| DRAWN BY | E.E.S. & R.E. Reid | | W. Wallace |
| TRACED BY | R.E. REID | ENGINEER IN CHARGE | Martin A. Fisher |
| CHECKED BY | R.R. Room | | ASS'T. CITY ENGINEER |

CITY OF DETROIT
 DEPARTMENT OF PUBLIC WORKS
 CITY ENGINEER'S OFFICE
 BUREAU OF DESIGN

EASTERN MARKET
 MISC. PAVING

| | | |
|----------------|----------------|----------------|
| DESIGN NO. 976 | SCALE 1" = 20' | DWG. NO. C-696 |
| PAGE NO. 57 | DATE DEC. 1944 | |