

January 12, 2022

The Honorable City Council
Attn: Office of the City Clerk
200 Coleman A. Young Municipal Center
Detroit, MI 48226

**RE: Petition for the Easement Encroachment Within Vacated Frank Street
Industry Detroit
950 Selden Street
City of Detroit, Wayne County, Michigan**

Honorable City Council:

QFactor in partnership with Invest Detroit and Midtown Detroit is petitioning to encroach within the easement retained over vacated Frank Street between 4th Street and the John C. Lodge Service Drive. The encroachment petition will allow for the following improvements:

Sheet C-4

1. Food truck hookups that will provide electrical and water service
2. Concrete steps adjacent to a new doorway
3. Aluminum poles bolted to the pavement for string lighting
4. Handrail and concrete ramp
5. Extended concrete curb
6. Trex decking laid flush with concrete pavement
7. Bicycle Racks
8. Stepped concrete curb
9. Handrail and concrete ramp

Sheet C-6

1. 23 LF Electrical conduit for food truck hookup
2. 23 LF Water lead for food truck hookup
3. 12" nyloplast stormwater inlet
4. 12" nyloplast stormwater inlet
5. 4 FT diameter stormwater manhole
6. 2 FT diameter catch basin
7. Trapped catch basin structure
8. 6 LF PVC stormwater pipe
9. 54 LF PVC stormwater pipe
10. 38 LF PVC stormwater pipe
11. 73 LF PVC stormwater pipe
12. 72 LF PVC stormwater pipe

Sheet C-12

1. Irrigation rotor heads as shown on the plan
2. 1.5" irrigation main line
3. Proposed irrigation valves
4. 6" sleeves for irrigation main line

Sheet EX-1


- C. Wall pack style LED building mounted lights (4 total)
- E. 3.25 FT tall LED bollard lights (7 total)
- F. 3.25 FT tall LED bollard lights (6 total)
- G. 12 FT tall post top LED lights (4 total)
- I. Lantern style LED building mounted lights (4 total)
- J. Linear LED light strips attached to the building canopy (3 total)



- **WHO:** Industry Detroit QOZB, LLC
- **WHAT:** Encroachment within vacated Frank Street / retained public utility easement
- **WHERE:** Encroachment of the retained public utility easement over the vacated Frank Street between 4th Street and the Lodge Service Drive.
- **WHEN:** We are requesting to start the process immediately so that it does not slow the on-going improvements of the Jefferson School Building.
- **WHY:** The request is being made to enhance the vacated ROW area into an outdoor space for tenants as well as the surrounding community.

Thank you for your consideration,

Eric Williams, PE
ewilliams@stonefieldeng.com
Stonefield Engineering and Design, LLC



FRANK STREET COMMUNITY SPACE




SYMBOL	DESCRIPTION
---	PROPERTY LINE
---	SETBACK LINE
---	PROPOSED CURB
---	PROPOSED FLUSH CURB
---	PROPOSED EXTENDED CURB
○	PROPOSED SIGNS / BOLLARDS
■	PROPOSED BUILDING ADDITION
▨	PROPOSED CONCRETE PAVEMENT
▩	PROPOSED HERRINGBONE STAMPED CONCRETE PAVEMENT
▧	PROPOSED TREX DECKING
---	PROPOSED SCREENING FENCE
---	PROPOSED HANDRAIL
---	PROPOSED BUILDING DOOR
---	PROPOSED LIGHT POLE
---	PROPOSED ASPHALT OVERLAY



STONEFIELD
engineering & design

Detroit, MI - New York, NY - Rutherford, NJ
Princeton, NJ - Tampa, FL - Boston, MA
www.stonefieldeng.com


607 Shelby Suite 200, Detroit, MI 48226
Phone 248.247.1115



Client
QFactor / Invest Detroit
/ Midtown Detroit

950 Selden St.
Detroit, MI 48201

Key Plan



REVISION	DATE
1	12/16/2021
2	11/17/2021
3	09/29/2021

INDUSTRY Detroit

Drawing Title

SITE PLAN

Project Number: DET-20015

Drawn By: KTH/ERW Approved By: JRC


Scale: 1" = 30'-0"

Seal:



Drawing No:

Signature:

Drawing No:



SU-30 TRUCK TURN EXHIBIT



SU-30 - Single Unit Truck

Overall Length: 30,000ft
Overall Width: 8,000ft
Overall Body Height: 13,500ft
Min Body Ground Clearance: 1.367ft
Track Width: 8,000ft
Lock-to-lock time: 5.00s
Max Steering Angle (Virtual): 31.80°

LAND USE AND ZONING

SPECIAL DEVELOPMENT DISTRICT, MIXED-USE (SD-2)

PROPOSED USE	REQUIRED	PROPOSED
PARKING AREA		
ZONING REQUIREMENT		
MINIMUM LOT AREA	N/A	3.04 AC (132,510 SF)
MINIMUM LOT WIDTH	N/A	107.9 FT
MINIMUM LOT DEPTH	N/A	312.5 FT
MINIMUM FRONT YARD SETBACK	12 FT (1)	12.8 FT
MINIMUM SIDE YARD SETBACK	N/A	0.0 FT (EN)
MINIMUM R.O.W. LANDSCAPE STRIP	5 FT	0.0 FT (EN)
MINIMUM RESIDENTIAL PARKING SETBACK	10 FT	1.4 FT (EN)

(1) SEC 50-1-1-245: MAXIMUM FRONT SETBACK IS THE AVERAGE FRONT SETBACK OF BUILDINGS ON EACH SIDE OF PROPERTY

(EN) EXISTING NON-COMFORMITY

OFF-STREET PARKING REQUIREMENTS


CODE SECTION	REQUIRED	PROPOSED
§ 50-14-49	COMMERCIAL USE (1)	113 SPACES
	TOTAL: 195 SPACES	
§ 50-14-231	PARKING DIMENSIONS: (2)	9 FT X 20 FT
	9 FT X 20 FT W/ 20 FT AISLE	W/ 20 FT AISLE
§ 50-14-343	INTERIOR LANDSCAPING: (1) (1) SPACES (2) 36 SPACES = 2,442 SF	3,511 SF

(1) PER APPROVAL LETTER RECEIVED 7/9/2020, BSEED CAN SUBTRACT 65 REQUIRED SPACES FROM THE PROPOSED LAND USE PARKING REQUIREMENT

(2) PARKING LENGTH MAY BE REDUCED BY 2 FEET WHEN ABUTTING LANDSCAPING, PROVIDED A 6" CURB/WHEEL STOP

LEGEND

▲ = REVISION NUMBER




BASIS OF BEARING
NORTH 67°13'00" EAST, BEING THE SOUTHERLY RIGHT OF WAY LINE OF FRANK STREET AS RECORDED IN BOOK 7 OF PLATS, PAGE 5, WAYNE COUNTY RECORDS.

BENCHMARKS
SITE BENCHMARK #1
TOP OF ARROW ON FIRE HYDRANT, LOCATED IN THE NORTH RIGHT OF WAY OF FRANK STREET APPROXIMATELY 83' EAST OF JOHN C. LODGE FREEWAY.
ELEVATION = 620.19 (NAVD 88 DATUM)
SITE BENCHMARK #2
TOP OF ARROW ON FIRE HYDRANT, LOCATED IN THE NORTH RIGHT OF WAY OF SELDEN STREET APPROXIMATELY 102' EAST OF JOHN C. LODGE FREEWAY.
ELEVATION = 618.27 (NAVD 88 DATUM)
SITE BENCHMARK #3
NAIL ON UTILITY POLE APPROXIMATELY 24 FEET NORTHWEST OF SOUTHWEST PROPERTY CORNER.
ELEVATION = 619.47 (NAVD 88)

MANHOLE SCHEDULE


SEWER MANHOLE #30161 RIP#6165 INV. 15' S=604.07 INV. 12' NE=610.05 INV. 12' SE=608.40	SEWER MANHOLE #30381 RIP#6173 UNABLE TO OPEN	CATCH BASIN #35003 RIP#6173 TOP OF DEBRIS=613.23 VERT. DROP
SEWER MANHOLE #30424 RIP#6167 UNABLE TO OPEN	SEWER MANHOLE #30304 RIP#6167 INV. 12' S=606.06 INV. 12' SW=607.26 INV. 30' W=608.40 INV. 12' N=610.36	CATCH BASIN #35000 RIP#6167 VERT. DROP
SEWER MANHOLE #30204 RIP#6152 INV. 12' NE=609.52 INV. 12' SW=607.07 INV. 12' SW=606.06 INV. 8' W=606.86 INV. 8' N=604.92 INV. 12' N=603.00 INV. 30' W=608.40 INV. 30' S=598.82 INV. 12' SE=609.24	SEWER MANHOLE #30317 RIP#6167 INV. 12' NE=611.75 INV. 12' NW=611.77 INV. 30' W=601.40 TOP OF DEBRIS=611.90	CATCH BASIN #35125 RIP#6167 VERT. DROP
SEWER MANHOLE #30291 RIP#6179 UNABLE TO OPEN	CATCH BASIN #20121 RIP#6173 INV. 4' SW=614.68	CATCH BASIN #35003 RIP#6167 TOP OF DEBRIS=613.23
SEWER MANHOLE #30438 RIP#6158 UNABLE TO OPEN	CATCH BASIN #20290 RIP#6172 TOP OF DEBRIS=612.82	CATCH BASIN #30316 RIP#6158 TOP OF DEBRIS=610.72
	CATCH BASIN #20336 RIP#6167 TOP OF DEBRIS=611.20	CATCH BASIN #30314 RIP#6158 INV. 12' N=610.33
	CATCH BASIN #20353 RIP#6174 INV. 12' S=611.19	CATCH BASIN #30303 RIP#6157 INV. 12' SW=609.42
		CATCH BASIN #30300 RIP#6174 TOP OF DEBRIS=614.76



SYMBOL DESCRIPTION

---	PROPERTY LINE
---	PROPOSED GRADING CONTOUR
---	PROPOSED GRADING RIDGELINE
---	PROPOSED DIRECTION OF DRAINAGE FLOW
X G 100.00	PROPOSED GRADE SPOT SHOT
X TC 100.50 BC 100.00	PROPOSED TOP OF CURB / BOTTOM OF CURB SPOT SHOT
X FC 100.00	PROPOSED FLUSH CURB SPOT SHOT
X TS 100.50 X STEPS@6" BS 100.00	PROPOSED TOP STEP / BOTTOM STEP SPOT SHOT

FRANK STREET COMMUNITY SPACE
GRAPHIC SCALE IN FEET
1" = 20'




STATIONING PROFILE VIEW FROM EXISTING BUILDING NORTH TO FRANK STREET (SECTION A-A')
GRAPHIC SCALE IN FEET
1" = 20'

PROFILE LEGEND

---	EXISTING SIDEWALK GRADE
---	PROPOSED SIDEWALK GRADE

VERTICAL SCALE **HORIZONTAL SCALE**



LEGEND

#	= REVISION NUMBER
---	-------------------

- GRADING NOTES**
- ALL SOIL AND MATERIAL REMOVED FROM THE SITE SHALL BE DISPOSED OF IN ACCORDANCE WITH LOCAL STATE AND FEDERAL REQUIREMENTS. ANY GROUNDWATER DEWATERING PRACTICES SHALL BE PERFORMED UNDER THE SUPERVISION OF A QUALIFIED PROFESSIONAL. THE CONTRACTOR IS REQUIRED TO OBTAIN ALL NECESSARY PERMITS FOR THE DISCHARGE OF DEWATERED GROUNDWATER. ALL SOIL IMPORTED TO THE SITE SHALL BE CERTIFIED CLEAN FILL. CONTRACTOR SHALL MAINTAIN RECORDS OF ALL FILL MATERIALS BROUGHT TO THE SITE.
 - THE CONTRACTOR IS REQUIRED TO PROVIDE TEMPORARY AND/OR PERMANENT SHORING WHERE REQUIRED DURING EXCAVATION ACTIVITIES INCLUDING BUT NOT LIMITED TO UTILITY TRENCHES, TO ENSURE THE STRUCTURAL INTEGRITY OF NEARBY STRUCTURES AND STABILITY OF THE SURROUNDING SOILS.
 - PROPOSED TOP OF CURB ELEVATIONS ARE GENERALLY 4 INCHES TO 7 INCHES ABOVE EXISTING GRADES UNLESS OTHERWISE NOTED. THE CONTRACTOR WILL SUPPLY ALL STAKED-OUT CURB GRADE SHEETS TO STONEFIELD ENGINEERING & DESIGN, LLC FOR REVIEW AND APPROVAL PRIOR TO POURING CURBS.
 - THE CONTRACTOR IS RESPONSIBLE TO SET ALL PROPOSED UTILITY COVERS AND RESET ALL EXISTING UTILITY COVERS WITHIN THE PROJECT LIMITS TO PROPOSED GRADE IN ACCORDANCE WITH ANY APPLICABLE MUNICIPAL, COUNTY, STATE AND/OR UTILITY AUTHORITY REGULATIONS.
 - MINIMUM SLOPE REQUIREMENTS TO PREVENT PONDING SHALL BE AS FOLLOWS:
• CURB GUTTER: 0.50%
• CONCRETE SURFACES: 1.00%
• ASPHALT SURFACES: 1.00%
 - A MINIMUM SLOPE OF 1.00% SHALL BE PROVIDED AWAY FROM ALL BUILDINGS. THE CONTRACTOR SHALL ENSURE POSITIVE DRAINAGE FROM THE BUILDING TO AN ACCESSIBLE RAMP, AT ACCESSIBLE BUILDING ENTRANCES, AT AN AREA IN FRONT OF A WALK-UP PATH, AND AT TURNING SPACES ALONG THE ACCESSIBLE PATH OF TRAVEL. THE LANDING AREA SHALL HAVE A MINIMUM CLEAR AREA OF 60 INCHES UNLESS INDICATED OTHERWISE WITHIN THE PLAN SET.
 - THE CONTRACTOR SHALL MAINTAIN A MAXIMUM 8.33% RUNNING SLOPE AND A MAXIMUM 2.00% CROSS SLOPE ON ANY CURB RAMP ALONG THE ACCESSIBLE PATH OF TRAVEL. WHERE PROVIDED, CURB RAMP FLARES SHALL NOT HAVE A SLOPE GREATER THAN 1:10.00 IF A LANDING AREA IS PROVIDED AT THE TOP OF THE RAMP. CURB RAMP FLARES SHALL NOT HAVE A SLOPE GREATER THAN 8.33% IF A LANDING AREA IS NOT PROVIDED AT THE TOP OF THE RAMP. CURB RAMP FLARES SHALL NOT RISE MORE THAN 6 INCHES IN ELEVATION WITHOUT A HANDRAIL. THE CLEAR WIDTH OF A CURB RAMP SHALL BE NO LESS THAN 36 INCHES WIDE.
 - ACCESSIBLE RAMP WITH A RISE GREATER THAN 4 INCHES SHALL CONTAIN COMPLIANT HANDRAILS ON BOTH SIDES OF THE RAMP AND SHALL NOT RISE MORE THAN 30" IN ELEVATION WITHOUT A LANDING AREA IN BETWEEN RAMP RUNS. LANDING AREAS SHALL ALSO BE PROVIDED AT THE TOP AND BOTTOM OF THE RAMP.
 - A SLIP RESISTANT SURFACE SHALL BE CONSTRUCTED ALONG THE ACCESSIBLE PATH AND WITHIN ADA PARKING AREAS.
 - THE CONTRACTOR SHALL ENSURE A MAXIMUM OF 1/4" INCHES VERTICAL CHANGE IN LEVEL ALONG THE ACCESSIBLE PATH, WHERE A CHANGE BETWEEN 1/4" INCHES AND 1/2" INCHES EXISTS. CONTRACTOR SHALL ENSURE THAT THE TOP 1/4" INCH CHANGE IN LEVEL IS BEVELED WITH A SLOPE NOT STEEPER THAN 1 UNIT HORIZONTAL AND 2 UNITS HORIZONTAL (2:1 SLOPE).
 - THE CONTRACTOR SHALL ENSURE THAT ANY OPENINGS (GAPS OR HORIZONTAL SEPARATION) ALONG THE ACCESSIBLE PATH SHALL NOT ALLOW PASSAGE OF A SPHERE GREATER THAN 1/4" INCH.

- ADA NOTES**
- THE CONTRACTOR SHALL MAINTAIN A MAXIMUM 2.00% SLOPE IN ANY DIRECTION WITHIN THE ADA PARKING SPACES AND ACCESSIBLE AREAS.
 - THE CONTRACTOR SHALL PROVIDE COMPLIANT SIGNAGE AT ALL ADA PARKING AREAS IN ACCORDANCE WITH STATE GUIDELINES.
 - THE CONTRACTOR SHALL MAINTAIN A MAXIMUM 5.00% RUNNING SLOPE AND A MAXIMUM OF 2.00% CROSS SLOPE ALONG WALKWAYS WITHIN THE ACCESSIBLE PATH OF TRAVEL (SEE THE SITE PLAN FOR THE LOCATION OF THE ACCESSIBLE PATH). THE CONTRACTOR IS RESPONSIBLE TO ENSURE THE ACCESSIBLE PATH OF TRAVEL IS 36 INCHES WIDE OR GREATER UNLESS INDICATED OTHERWISE WITHIN THE PLAN SET.
 - THE CONTRACTOR SHALL MAINTAIN A MAXIMUM 2.00% SLOPE IN ANY DIRECTION AT ALL LANDINGS. LANDINGS INCLUDE, BUT ARE NOT LIMITED TO, THE TOP AND BOTTOM OF AN ACCESSIBLE RAMP, AT ACCESSIBLE BUILDING ENTRANCES, AT AN AREA IN FRONT OF A WALK-UP PATH, AND AT TURNING SPACES ALONG THE ACCESSIBLE PATH OF TRAVEL. THE LANDING AREA SHALL HAVE A MINIMUM CLEAR AREA OF 60 INCHES UNLESS INDICATED OTHERWISE WITHIN THE PLAN SET.
 - THE CONTRACTOR SHALL MAINTAIN A MAXIMUM 8.33% RUNNING SLOPE AND A MAXIMUM 2.00% CROSS SLOPE ON ANY CURB RAMP ALONG THE ACCESSIBLE PATH OF TRAVEL. WHERE PROVIDED, CURB RAMP FLARES SHALL NOT HAVE A SLOPE GREATER THAN 1:10.00 IF A LANDING AREA IS PROVIDED AT THE TOP OF THE RAMP. CURB RAMP FLARES SHALL NOT HAVE A SLOPE GREATER THAN 8.33% IF A LANDING AREA IS NOT PROVIDED AT THE TOP OF THE RAMP. CURB RAMP FLARES SHALL NOT RISE MORE THAN 6 INCHES IN ELEVATION WITHOUT A HANDRAIL. THE CLEAR WIDTH OF A CURB RAMP SHALL BE NO LESS THAN 36 INCHES WIDE.
 - ACCESSIBLE RAMP WITH A RISE GREATER THAN 4 INCHES SHALL CONTAIN COMPLIANT HANDRAILS ON BOTH SIDES OF THE RAMP AND SHALL NOT RISE MORE THAN 30" IN ELEVATION WITHOUT A LANDING AREA IN BETWEEN RAMP RUNS. LANDING AREAS SHALL ALSO BE PROVIDED AT THE TOP AND BOTTOM OF THE RAMP.
 - A SLIP RESISTANT SURFACE SHALL BE CONSTRUCTED ALONG THE ACCESSIBLE PATH AND WITHIN ADA PARKING AREAS.
 - THE CONTRACTOR SHALL ENSURE A MAXIMUM OF 1/4" INCHES VERTICAL CHANGE IN LEVEL ALONG THE ACCESSIBLE PATH, WHERE A CHANGE BETWEEN 1/4" INCHES AND 1/2" INCHES EXISTS. CONTRACTOR SHALL ENSURE THAT THE TOP 1/4" INCH CHANGE IN LEVEL IS BEVELED WITH A SLOPE NOT STEEPER THAN 1 UNIT HORIZONTAL AND 2 UNITS HORIZONTAL (2:1 SLOPE).
 - THE CONTRACTOR SHALL ENSURE THAT ANY OPENINGS (GAPS OR HORIZONTAL SEPARATION) ALONG THE ACCESSIBLE PATH SHALL NOT ALLOW PASSAGE OF A SPHERE GREATER THAN 1/4" INCH.

Hamilton Anderson Associates, Inc.
1435 Randolph Suite 200
Detroit, Michigan 48226
p 313 964 0270 f 313 964 0170
www.hamilton-anderson.com

MEP Engineer: MEP Engineering
6402 S Troy Cir.
Centennial, CO 80111
303.936.1633
Structural Engineer: SDI Structures
275 Liberty
Ann Arbor, MI 48104
734.213.6090
Civil Engineer: Stonefield Engineering
607 Shelby St. # 200
Detroit, MI 48226
248.247.1115




Stonefield Engineering & Design
Detroit, MI - New York, NY - Rutherford, NJ
Pawson, NJ - Tampa, FL - Boston, MA
www.stonefieldeng.com

607 Shelby Suite 200, Detroit, MI 48226
Phone 248.247.1115



Client: QFactor / Invest Detroit / Midtown Detroit
950 Selden St.
Detroit, MI 48201



PERMIT REVISIONS


CD PROGRESS SET	12/16/2021
PERMIT SET	11/17/2021
PERMIT SET	05/26/2021

Project
INDUSTRY Detroit


Drawing Title: GRADING PLAN

Project Number: DET-20015
Drawn By: KTH/ERW Approved By: JRC
Scale: 1" = 30'-0"


Signature: _____
Date: _____
Drawing No: _____




UTILITY TRENCH DETAIL
NOT TO SCALE




THRUST BLOCK DETAIL
NOT TO SCALE





VALVE BOX DETAIL
NOT TO SCALE




WATTS PRESSURE REDUCER DETAIL
NOT TO SCALE




ECLIPSE NO. 85 BLOW-OFF HYDRANT
NOT TO SCALE



WABASH BOX DETAIL
NOT TO SCALE



RESIDENTIAL CONNECTION
NOT TO SCALE



- IRRIGATION NOTES:**
- SYSTEM WAS DESIGNED TO ASSUME 50 PSI, 1" SERVICE LINE, 1" METER AND 24 GALLONS PER MINUTE AND LOAM TYPE SOILS. ALTERATIONS MAY BE NEEDED BASED ON SITE CONDITIONS.
 - A FLOW TEST SHALL BE PERFORMED ON SITE PRIOR TO INSTALLATION TO CONFIRM STATIC PSI.
 - APPROVED ALTERNATES TO BE SUBMITTED AND APPROVED.
 - 1 1/2" NPT BACKFLOW PREVENTOR TO BE INSTALLED AS PER LOCAL PLUMBING CODES.
 - MAIN LINE PIPE AND WIRE TO BE TRENCHED 18" BELOW FINISH GRADE. BACKFILL MATERIAL SHALL BE FREE OF ALL ROCKS, TAMP TO 95% COMPACTION IN 6" LIFTS. ALL GRADING OVER THE IRRIGATION LINES SHALL BE FLUSH WITH THE ADJACENT SOIL AND BE FREE OF ROCKS AND DEBRIS. LATERAL PIPE TO BE 12" BELOW FINISH GRAD. TAMP AND RAKE FLOWED AREAS. REMOVE ANY LARGE ROCKS AND FILL ANY VOIDS.
 - DRIP TUBING SHALL BE 3" BELOW FINISHED SOIL GRADE AND SPACED EVERY 24" MINIMUM. ROW SPACING IN GROUND COVER TO BE 18". ALL SHRUBS TO HAVE TWO ROWS OF DRIP TUBE. FOLLOW MANUFACTURERS DESIGN SPECIFICATION FOR LOCATION OF HEADERS. MAXIMUM LENGTH OF END FED TUBING, AND INSTALLATION GUIDELINES.
 - IRRIGATION CONTRACTOR IS RESPONSIBLE FOR COORDINATING EXISTING UTILITY LOCATIONS WITH THE CALL BEFORE YOU DIG SERVICE AND SITE SUBCONTRACTORS.
 - ALL ELECTRIC ZONE VALVES TO BE PLACED BELOW GRADE IN APPROPRIATELY SIZED VALVE BOXES AND WITH MULCHED BEDS.
 - CONTRACTOR TO SUPPLY 100% COVERAGE GUARANTEE.
 - LOCATION OF CONTROLLER, BACKFLOW DEVICE, MASTER VALVE AND RAIN SENSOR ARE CONCEPTUAL. ACTUAL LOCATION TO BE DETERMINED ON SITE BASED UPON EXISTING CONDITIONS.
 - ALL PROPOSED LANDSCAPING TO BE IRRIGATED BY A 100% AUTOMATIC SYSTEM.
 - IRRIGATION SYSTEM SHALL NOT BE INSTALLED THROUGH EXISTING PLANT COMMUNITIES.
 - IRRIGATION SPRINKLER ZONES TO BE SEPARATE FOR HIGH AND LOW WATER REQUIREMENT PLANT AREAS AND OPERATED ON DIFFERENT WATERING SCHEDULES.
 - IRRIGATION OVERTHROW TO NON-PERVIOUS AND NATURAL AREAS TO BE MINIMIZED.
 - A RAIN SENSOR IS TO BE INSTALLED WITH THE IRRIGATION SYSTEM CONTROLLER.
 - IRRIGATION PIPING TO BE LOCATED WITHIN PLANTING OR SOD AREAS WHEREVER FEASIBLE. PIPING UNDER LOADS TO BE INSTALLED WITHIN SCHEDULE 40 PVC SLEEVE.
 - ALL TREE SHRUB AND GROUND COVER AREAS ARE TO BE FULLY IRRIGATED WITH DRIP MICRO IRRIGATION. LOW-VOLUME EMITTERS. ALL SOD AREAS TO BE IRRIGATED WITH ROTOR OR SPRAY HEAD SPRINKLERS SPACED TO PROVIDE 100% COVERAGE.
 - A 1" TYP. FILTER SHALL BE INSTALLED AT THE HEAD END OF LOW VOLUME LINES AND IN-LINE PRESSURE REGULATORS TO REDUCE PRESSURE NO MORE THAN 15 PSI SHALL BE UTILIZED.
 - NON-POTABLE IRRIGATION LINES TO BE PURPLE IN COLOR.
 - WHEN NECESSARY, IRRIGATION INSTALLATION WITHIN THE DRIFLINE/CANOPY OF EXISTING TREES SHOULD BE DONE IN THE MOST SENSITIVE MANNER POSSIBLE IN ORDER TO AVOID ROOT DAMAGE. PROPOSED IRRIGATION WITHIN THE DRIFLINE/CANOPY SHOULD BE MICRO-SPRAY LOCATED ABOVE EXISTING GRADE.
 - THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING THE COMPLETE DESIGN AND CONSTRUCTION OF AN IRRIGATION SYSTEM FOR THE PROJECT, INCLUDING ALL PIPING, VALVES, HEADS, SLEEVES, AND WIRING. THE CONTRACTOR SHALL ALSO PERMIT AND PROVIDE AN IRRIGATION WELL AND CONTROLLER SYSTEM INCLUDING ALL NECESSARY POWER. THE SYSTEM SHALL BE DESIGNED TO SUPPLY SUFFICIENT IRRIGATION TO ALL PLANTING AREAS ACROSS THE ENTIRE SITE TO SUPPORT THE GROWTH AND MAINTENANCE OF THE LANDSCAPING. THE CONTRACTOR SHALL SUBMIT TO THE LANDSCAPE ARCHITECT, AS SHOWN DRAWING, THE DETAILED LAYOUT OF THE SYSTEM FOR REVIEW AND APPROVAL BY THE LANDSCAPE ARCHITECT.

HamiltonAnderson
architecture landscape architecture urban design

Hamilton Anderson Systems, Inc
1435 Randolph Suite 200
Detroit, Michigan 48226
p 313 964 0270 f 313 964 0170
www.hamilton-anderson.com

MEP Engineer
6402 S Troy Cir.
Centennial, CO 80111
303.936.1633

Structural Engineer
SDI Structures
275 Liberty
Ann Arbor, MI 48104
734.213.6090

Civil Engineer
Stonefield Engineering
607 Shelby St. # 200
Detroit, MI 48226
248.247.1115

STONEFIELD
engineering & design

Detroit, MI - New York, NY - Rutherford, NJ
Princeton, NJ - Tampa, FL - Boston, MA
www.stonefieldeng.com

607 Shelby Suite 200, Detroit, MI 48226
Phone 248.247.1115

Client
QFactor / Invest Detroit
/ Midtown Detroit

950 Selden St.
Detroit, MI 48201

Key Plan

INDUSTRY Detroit

Drawing Title
IRRIGATION PLAN (NORTH)


Project Number: DET-20015
Drawn By: KTH/ERW Approved By: JRC
Scale: 1" = 20'-0"

Seal:

Signature: _____
Date: _____















Drawing No: _____

C-11




MUTCD NUMBER	TEXT	COLOR	SIZE OF SIGN (WIDTH X HEIGHT)	TYPE OF MOUNT
STOP SIGN (R1-1)	STOP	WHITE	36" X 36"	GROUND

SIGN DATA TABLE
NOT TO SCALE




PERMIT REVISIONS	DATE
CD PROGRESS SET	11/17/2021
PERMIT SET	05/26/2021

Project




CURB RAMP DETAIL
NOT TO SCALE

- NOTES:
- CROSS SLOPE ON RAMP SHALL NOT EXCEED 2%
 - A FLUSH CURB SHALL HAVE A MINIMUM WIDTH OF 36". SEE PLAN FOR EXACT WIDTH.
 - RAMP SHALL HAVE A MAXIMUM RISE OF 6" WITHOUT A HANDRAIL.




ACCESSIBLE ENTRANCE LANDING DETAIL
NOT TO SCALE

- NOTES:
- MAXIMUM SLOPE ON LANDING SHALL BE 1:50 IN ALL DIRECTIONS
 - DIMENSIONS SHOWN HERE ARE THE MINIMUM DIMENSIONS REQUIRED FOR AN ADA COMPLIANT LANDING AT THE ACCESSIBLE ENTRANCE. REFER TO SITE PLAN FOR SITE SPECIFIC DIMENSIONS THAT MAY SPECIFY A LARGER LANDING AREA.
 - CONTRACTOR SHALL CONTACT THE ENGINEER BEFORE CONSTRUCTION IF THE ACCESSIBLE ENTRANCE ON SITE DOES NOT MATCH THE SCENARIO SHOWN ABOVE.




CONCRETE STEP & ELEVATED LANDING DETAIL
NOT TO SCALE

- NOTES:
- CONTRACTOR SHALL ENSURE 3" MINIMUM EMBEDMENT FOR REBAR EXPOSED TO EARTH AND 2" MINIMUM EMBEDMENT FOR REBAR EXPOSED TO WEATHER SURFACE. NOISING REBAR TO BE EMBEDDED 1 1/2"
 - CONTRACTOR SHALL MAINTAIN A MAXIMUM 1:50 SLOPE IN ALL DIRECTIONS WITHIN PROPOSED CONCRETE LANDINGS.
 - STAIR TREAD TO BE ANPET SERIES 500 MODEL 11 OR APPROVED EQUIVALENT.




CONCRETE STEPS & ELEVATED LANDING DETAIL
NOT TO SCALE

- NOTES:
- CONTRACTOR SHALL ENSURE 3" MINIMUM EMBEDMENT FOR REBAR EXPOSED TO EARTH AND 2" MINIMUM EMBEDMENT FOR REBAR EXPOSED TO WEATHER SURFACE. NOISING REBAR TO BE EMBEDDED 1 1/2"
 - CONTRACTOR SHALL MAINTAIN A MAXIMUM 1:50 SLOPE IN ALL DIRECTIONS WITHIN PROPOSED CONCRETE LANDINGS.
 - STEPS IN SERIES SHALL HAVE UNIFORM RISE HEIGHT.




CLEAN-OUT
NOT TO SCALE




UTILITY TRENCH DETAIL
NOT TO SCALE

- NOTE:
- MINIMUM PIPE COVER SHALL BE AS FOLLOWS:
- ELECTRIC SERVICE - PER APPLICABLE UTILITY AUTHORITY
 - GAS SERVICE - PER APPLICABLE UTILITY AUTHORITY
 - SEWER SERVICE - 36" MINIMUM
 - WATER SERVICE - 48" MINIMUM




STORM TRENCH DETAIL
NOT TO SCALE

- NOTES:
- ALL PIPE SYSTEM INSTALLATIONS SHALL MEET ALL APPLICABLE STANDARDS AND SPECIFICATIONS.
 - ALL HOPE PIPE SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D3213 STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF THERMOPLASTIC PIPE FOR SEWERS AND OTHER GRAVITY FLOW APPLICATIONS (LATEST EDITION).
 - ALL RCP PIPE SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH ASTM C754 STANDARD SPECIFICATION FOR REINFORCED CONCRETE CULVERT, STORM DRAIN, AND SEWER PIPE (LATEST EDITION).
 - FOR NON HOPE OR RCP PIPE INSTALLATIONS, CONTRACTOR SHALL INSTALL PIPE IN ACCORDANCE WITH ALL APPLICABLE STANDARDS AND SPECIFICATIONS.
 - WHERE THE TRENCH BOTTOM IS UNSTABLE, CONTRACTOR SHALL PROVIDE SUITABLE BACKFILL MATERIAL AS REQUIRED BY ENGINEER OR PER GEOTECH RECOMMENDATIONS.
 - MINIMUM COVER IN TRAFFIC AREAS IS 12" UP TO 48" DIAMETER PIPE AND 24" FOR 54" - 60" DIAMETER PIPE TO BOTTOM OF FLEXIBLE PAVEMENT OR TOP OF RIGID PAVEMENT.
 - CONTRACTOR SHALL INSTALL SUITABLE MATERIAL FOR INITIAL AND FINAL BACKFILL. BACKFILL COMPACTION SHOULD MEET ALL APPLICABLE STANDARDS AND SPECIFICATIONS.




ELECTRICAL CONDUIT TRENCH DETAIL
NOT TO SCALE

- NOTES:
- ALL PIPE SYSTEM INSTALLATIONS SHALL MEET ALL APPLICABLE STANDARDS AND SPECIFICATIONS.
 - ALL HOPE PIPE SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D3213 STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF THERMOPLASTIC PIPE FOR SEWERS AND OTHER GRAVITY FLOW APPLICATIONS (LATEST EDITION).
 - ALL RCP PIPE SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH ASTM C754 STANDARD SPECIFICATION FOR REINFORCED CONCRETE CULVERT, STORM DRAIN, AND SEWER PIPE (LATEST EDITION).
 - FOR NON HOPE OR RCP PIPE INSTALLATIONS, CONTRACTOR SHALL INSTALL PIPE IN ACCORDANCE WITH ALL APPLICABLE STANDARDS AND SPECIFICATIONS.
 - WHERE THE TRENCH BOTTOM IS UNSTABLE, CONTRACTOR SHALL PROVIDE SUITABLE BACKFILL MATERIAL AS REQUIRED BY ENGINEER OR PER GEOTECH RECOMMENDATIONS.
 - MINIMUM COVER IN TRAFFIC AREAS IS 12" UP TO 48" DIAMETER PIPE AND 24" FOR 54" - 60" DIAMETER PIPE TO BOTTOM OF FLEXIBLE PAVEMENT OR TOP OF RIGID PAVEMENT.
 - CONTRACTOR SHALL INSTALL SUITABLE MATERIAL FOR INITIAL AND FINAL BACKFILL. BACKFILL COMPACTION SHOULD MEET ALL APPLICABLE STANDARDS AND SPECIFICATIONS.




LIGHT POLE INSTALLATION DETAIL
NOT TO SCALE

- NOTES:
- MINIMUM SOIL BEARING PRESSURE OF 1500 PSF. SOIL FRICTION ANGLE OF 30 DEGREES, AND SOIL DRY UNIT WEIGHT OF 120 PCF SHALL BE CONFIRMED IN THE FIELD BY A QUALIFIED PROFESSIONAL.
 - CAST-IN-PLACE CONCRETE SHALL BE CONSOLIDATED USING VIBRATOR.
 - ALL REBAR TO BE NEW GRADE 60 STEEL.
 - PRE-CAST PIERS ACCEPTABLE UPON WRITTEN APPROVAL OF SHOP DRAWING BY ENGINEER.
 - CONCRETE TO BE INSTALLED A MINIMUM OF 28 DAYS PRIOR TO INSTALLING LIGHT POLE. POURED CONCRETE MIX REQUIRED TO OBTAIN 80% OF DESIGN STRENGTH PRIOR TO INSTALLING LIGHT POLE.
 - CONCRETE SHALL HAVE A MAXIMUM SLOPE OF 4" WITHIN 1' TOLERANCE.
 - POLE SHALL BE RATED FOR 10 MPH HIGHER THAN MAXIMUM WIND SPEED 33FT ABOVE GROUND FOR THE AREA BASED ON ANSISANCE 7-93.
 - POLE TO BE TERMINATED AT A FORM.
 - WORK SHALL CONFORM TO ACI BEST PRACTICES FOR APPROPRIATE TEMPERATURE AND WEATHER CONDITIONS.
 - CONTRACTOR TO TEMPORARILY SUPPORT ADJACENT SOIL AND STRUCTURES DURING EXCAVATION IF REQUIRED.




TYPICAL DETAIL FOR GUARD RAILING AFF NO MORE THAN 30"

HAND RAIL DETAIL
NOT TO SCALE



FOOD TRUCK HOOKUP DETAIL (OR APPROVED ALTERNATE)
NOT TO SCALE


- NOTES:
- SEE SITE PLAN FOR LOCATION.
 - SEE MEP PLAN FOR INTERIOR SHUTOFF VALVE AND BACKFLOW PREVENTER FOR WATER SERVICE.
 - SEE MEP PLAN FOR ELECTRICAL DETAILS.




CONNECTION, SADDLE TO LATERAL SEWER

- NOTES:
- FOR SEWERS 18" OR LESS 4" SADDLE MAY BE USED IF THE OUTSIDE DIA. OF THE TAP IS LESS THAN ONE HALF THE DIA. OF THE SEWER BEING TAPPED.
 - PROVIDE EXTENSION CLAMPS FOR 18" SEWERS AND LARGER.
 - CONCRETE BELOW PIPE IS ONLY REQUIRED FOR 18" SEWERS AND LARGER WITH STRAPS.

LEGEND
= REVISION NUMBER



RAISED METAL PLANTER
12" x 1'-0"



RAISED PLANTER - SECTION
3/4" x 1'-0"

- NOTES:
- ALL METAL COMPONENTS ARE TO BE POWDER COATED BLACK - POOB - BK08 "BLACK 80% GLOSS" PROVIDED BY CARDINAL INDUSTRIAL FINISHED OR APPROVED EQUAL. CONTRACTOR TO SUBMIT SAMPLES TO LANDSCAPE ARCHITECT FOR APPROVAL.

PLANTING NOTES:


- LANDSCAPE CONTRACTOR SHALL LOCATE ALL TREES, SHRUBS AND PLANTING BEDS ACCORDING TO LOCATIONS SHOWN ON DRAWINGS. ALL PLANTING LOCATIONS SHALL BE SUBJECT TO REVIEW AND APPROVAL BY LANDSCAPE ARCHITECT/OWNER'S REPRESENTATIVE PRIOR TO THE START OF PLANTING OPERATIONS. CONTRACTOR SHALL MAKE MODIFICATIONS IN LOCATIONS AS DIRECTED BY LANDSCAPE ARCHITECT.
- THE PLANT SCHEDULE IS FOR CONTRACTOR'S CONVENIENCE ONLY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING EXISTING CONDITIONS AND REPORTING IN WRITING TO THE LANDSCAPE ARCHITECT ANY CONFLICTS RELATIVE TO IMPLEMENTATION OF THE LANDSCAPE CONSTRUCTION DOCUMENTS. VALERIAN LLC SHALL NOT ASSUME ANY ERRORS OR OMISSIONS IN THE PLANT SCHEDULE LISTED HEREIN. THE PLANT SYMBOLS SHOWN ON THE LANDSCAPE PLAN SHALL PREVAIL SHOULD THERE BE ANY DISCREPANCIES IN QUANTITIES BETWEEN THE PLAN AND PLANT SCHEDULE.
- LANDSCAPE CONTRACTOR SHALL PROVIDE PLANT PROTECTION AND MAINTENANCE THROUGHOUT INSTALLATION AND UNTIL FINAL ACCEPTANCE OF LANDSCAPE INSTALLATION AS FOLLOWS:
 - ALL PLANT MATERIAL SHALL BE PROTECTED, FROM TIME OF DIGGING TO TIME OF FINAL ACCEPTANCE, FROM INJURY, EXCESSIVE DRYING FROM WINDS, IMPROPER VENTILATION, OVER-WATERING, FREEZING, HIGH TEMPERATURES, OR ANY OTHER CONDITION DAMAGING TO PLANTS.
 - PLANT MATERIAL SHALL BE PLANTED ON THE DAY OF DELIVERY IF POSSIBLE. ALL PLANTS NOT PLANTED ON THE DAY OF DELIVERY SHALL BE PLACED IN A TEMPORARY NURSERY AND KEPT MOIST, SHADED, AND PROTECTED FROM THE SUN AND WIND. EACH ROOTBALL SHALL BE COVERED ENTIRELY WITH MULCH. ALL PLANT MATERIALS SHALL BE INSTALLED PER THE PLAN DRAWINGS AND SPECIFICATIONS.
 - LANDSCAPE CONTRACTOR SHALL PROVIDE PLANT MATERIALS THAT COMPLY WITH THE REQUIREMENTS OF THE MOST RECENT ANSI Z 60.1 STANDARDS FOR NURSERY STOCK UNLESS OTHERWISE SPECIFIED. CALIPER OF B&B TREES SHALL BE TAKEN 6 INCHES ABOVE THE GROUND UP TO AND INCLUDING 4 INCH CALIPER SIZE, AND 12 INCHES ABOVE THE GROUND FOR LARGER SIZES.
 - PLANTING MAINTENANCE SHALL INCLUDE WATERING, WEEDING, CULTIVATING, RESETTING PLANTS TO PROPER GRADES OR POSITION, REESTABLISHING SETTLED GRADES. HERBICIDE IS NOT RECOMMENDED FOR ONE YEAR FOLLOWING LANDSCAPE INSTALLATION.
 - PLANT MAINTENANCE SHALL INCLUDE THOSE OPERATIONS NECESSARY TO PROPER GROWTH AND SURVIVAL OF ALL PLANT MATERIALS. CONTRACTOR SHALL PROVIDE THIS WORK IN ADDITION TO SPECIFIC WARRANTY GUARANTEES.
- CONTRACTOR SHALL VERIFY AND MAINTAIN ALL SETBACKS, CLEAR ZONES AND SIGHT TRIANGLES REQUIRED BY ALL LOCAL AND MUNICIPAL CODES WHERE APPLICABLE.
- LANDSCAPE CONTRACTOR SHALL ENSURE THAT THE LANDSCAPE INSTALLATION IS COORDINATED WITH THE PLANS PREPARED BY OTHER CONSULTANTS SO THAT THE PROPOSED GRADING, STORM DRAINAGE OR OTHER PROPOSED CONSTRUCTION DOES NOT CONFLICT WITH NOR PRECLUDE INSTALLATION AND MAINTENANCE OF LANDSCAPE ELEMENTS AS DESIGNATED ON THIS PLAN.
- CONTRACTOR SHALL HAND DIG ALL PLANTING PITS ADJACENT TO UTILITIES. IF UTILITIES ARE DAMAGED REPAIRS SHALL BE MADE AT NO ADDITIONAL COST TO THE OWNER.



Client
QFactor / Invest Detroit / Midtown Detroit

950 Selden St
Detroit, MI 48201

Key Plan



REVISION	DATE	DESCRIPTION
1	09/20/21	ISSUED FOR PERMIT
2	11/17/2021	CD PROGRESS SET
3	05/26/2021	PERMIT SET

Project
INDUSTRY Detroit

Drawing Title

CONSTRUCTION DETAILS

Project Number: DET-20015

Drawn By: KTH/ERW Approved By: JRC




Scale: AS SHOWN

Seal:

Signature:

Drawing No:

13



Elastizell EF 30 PCF

Air added as aggregate

Air Water Mortar

On site production equipment for Elastizell EF

CLASS	MAXIMUM CAST DENSITY pcf (kg/m ³)	MINIMUM COMPRESSIVE STRENGTH* psi (Mpa)	ULTIMATE BEARING CAPACITY Tons/sf (kN/m ²)
I	24 (384)	10 (0.07)	07 (69)
II	30 (480)	40 (0.28)	2.9 (276)
III	36 (576)	80 (0.55)	5.8 (552)
IV	42 (672)	120 (0.83)	8.6 (827)
V	50 (800)	160 (1.10)	11.5 (1103)
VI	80 (1280)	300 (2.07)	21.6 (2068)

ELASTRIZELL LIGHTWEIGHT CONCRETE DETAIL (OR APPROVED ALTERNATE)

NOT TO SCALE

HAMILTONANDERSON
architecture landscape architecture urban design









Hamilton Anderson Associates, Inc
1435 Randolph Suite 200
Detroit, Michigan 48226
p 313 964 0270 f 313 964 0170
www.hamilton-anderson.com

MEP Engineer: MEI Engineering
Structural Engineer: SDI Structures
Civil Engineer: Stonefield Engineering

STONEFIELD
engineering & design

Detroit, MI - New York, NY - Rochester, NJ
Providence, RI - Tampa, FL - Boston, MA
www.stonefieldeng.com

607 Shelby Suite 200, Detroit, MI 48226
Phone 248.247.1115



Client: QFactor / Invest Detroit / Midtown Detroit

950 Selden St.
Detroit, MI 48201

Key Plan

PERMIT REVISIONS

NO.	DESCRIPTION	DATE
1	CD PROGRESS SET	12/16/2021
2	PERMIT SET	11/17/2021
3	PERMIT SET	05/26/2021

Project: **INDUSTRY Detroit**


Drawing Title: **CONSTRUCTION DETAILS**

Project Number: DET-20015
Drawn By: KTH/ERW Approved By: JRC
Scale: AS SHOWN
Seal:


Signature: _____
Drawing No: _____

C-15


PROPOSED LUMINAIRE SCHEDULE							
SYMBOL	LABEL	QUANTITY	SECURITY LIGHTING	DISTRIBUTION	LF	MANUFACTURER	IES FILE
	A	1	MIRADA LARGE LED AREA LIGHT - MINIMUM 40,000 LUMENS	SW	0.9	LSI	MRL-LED-40L-SIL-SW-LINV-40-70CRI
	B	3	MIRADA LARGE LED AREA LIGHT - MINIMUM 40,000 LUMENS	SW	0.9	LSI	MRL-LED-40L-SIL-SW-LINV-40-70CRI
	C	20	HAWK ENDURANCE WALL PACK (TYPE WLE) - 2,050 LUMENS	III	0.9	WAC	WP-LED227-AGH
	D	8	WALL WASH UP / DOWN FIXTURES	IV	0.9		
	E	7	MIMIK 20 BOLLARD LIGHT - 3K LUMENS LED	II	0.9	PIL	PL-07100_PIMIK_M_Type_3_20W_3000K_E_10V_1048F
	F	6	MIMIK 20 BOLLARD LIGHT - 3K LUMENS LED	IV	0.9	PIL	PL-07100_PIMIK_M_Type_3_20W_3000K_E_10V_1048F
	G	4	MIRADA MEDIUM POST TOP - 10K LUMENS LED	IV	0.9	LSI	MPP-LED-10L-SIL-FT-30-70CRI-H
	H	2	HINKLEY 2808DZ-LL OUTDOOR WALL LANTERN	V	0.9	HINKLEY	
	I	3	HINKLEY 2804OZ OUTDOOR WALL LANTERN	V	0.9	HINKLEY	
	J	3	HIGHLINER 2 LED LINEAR LIGHT	FT	0.9	SLOAN	



SYMBOL	DESCRIPTION
A (XX')	PROPOSED LIGHTING FIXTURE (MOUNTING HEIGHT)
'x'x	PROPOSED LIGHTING INTENSITY (FOOTCANDLES)
	PROPOSED AREA LIGHT
	PROPOSED BUILDING MOUNTED LIGHT
	PROPOSED STRING LIGHTS



LIGHT FIXTURES 'A' & 'B'



LIGHT FIXTURE 'C'



LIGHT FIXTURE 'D'



LIGHT FIXTURES 'E' & 'F'



LIGHT FIXTURE 'G'



LIGHT FIXTURE 'H'




LIGHT FIXTURE 'I'




LIGHT FIXTURE 'J'

- GENERAL LIGHTING NOTES**
- THE LIGHTING LEVELS DEPICTED WITHIN THE PLAN SET ARE CALCULATED UTILIZING DATA OBTAINED FROM THE LISTED MANUFACTURER. ACTUAL ILLUMINATION LEVELS AND PERFORMANCE OF ANY PROPOSED LIGHTING FIXTURE MAY VARY DUE TO UNCONTROLLABLE VARIABLES SUCH AS WEATHER, VOLTAGE SUPPLY, LAMP TOLERANCE, EQUIPMENT SERVICE LIFE AND OTHER VARIABLE FIELD CONDITIONS.
 - WHERE APPLICABLE THE EXISTING LIGHT LEVELS DEPICTED WITHIN THE PLAN SET SHALL BE CONSIDERED APPROXIMATE. THE EXISTING LIGHT LEVELS ARE BASED ON FIELD OBSERVATIONS AND THE MANUFACTURER'S DATA OF THE ASSUMED OR MOST SIMILAR LIGHTING FIXTURE MODEL.
 - UNLESS NOTED ELSEWHERE WITHIN THIS PLAN SET, THE LIGHT LOSS FACTORS USED IN THE LIGHTING ANALYSIS ARE AS FOLLOWS:
 - LIGHT EMITTING DIODES (LED): 0.90
 - HIGH PRESSURE SODIUM: 0.72
 - METAL HALIDE: 0.72
 - THE CONTRACTOR SHALL NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC IN WRITING PRIOR TO THE START OF CONSTRUCTION, OF ANY PROPOSED LIGHTING LOCATIONS THAT CONFLICT WITH EXISTING PROPOSED DRAINAGE UTILITY OR OTHER IMPROVEMENTS.
 - THE CONTRACTOR IS RESPONSIBLE TO PREPARE A WIRING PLAN AND PROVIDE ELECTRIC SERVICE TO ALL PROPOSED LIGHTING FIXTURES. THE CONTRACTOR IS REQUIRED TO PREPARE AN AS-BUILT PLAN OF WIRING AND PROVIDE COPIES TO THE OWNER AND STONEFIELD ENGINEERING & DESIGN, LLC.



Client
QFactor / Invest Detroit / Midtown Detroit
950 Selden St.
Detroit, MI 48201



PERMIT REVISIONS	DATE
CD PROGRESS SET	11/17/2021
PERMIT SET	05/26/2021

Project
INDUSTRY Detroit

Drawing Title

LIGHTING PLAN

Project Number: DET-20015

Drawn By: KTH/ERW Approved By: JRC

Scale: 1" = 30'-0"

Seal:

Signature:

Drawing No:

EX-1